



HEYD BESTELL-No.	GRÖSSE/SIZE			Abmessungen in mm / Dimensions in mm								kg/Stück
	d1	a	b	c	d2	d3	d4	d7	e	l	α	
AH32-2H-24x40 -01	24	16	24	95	40	16	M18x1,5 R	M12x1,5	65	20	35°	0,430
AH32-2H-24x40 -02	24	16	24	95	40	16	M18x1,5 L	M12x1,5	65	20	35°	0,430
AH32-2H-27x40 -01	27	20	27	100	45	18	M22x1,5 R	M14x1,5	70	22	40°	0,670
AH32-2H-27x40 -02	27	20	27	100	45	18	M22x1,5 L	M14x1,5	70	22	40°	0,670
AH32-2H-30x40 -01	30	22	29	105	52	20	M24x1,5 R	M16x1,5	75	24	40°	0,800
AH32-2H-30x40 -02	30	22	29	105	52	20	M24x1,5 L	M16x1,5	75	24	40°	0,800
AH32-2H-35x40 -01	35	25	33	115	62	22	M28x1,5 R	M18x1,5	80	26	40°	1,330
AH32-2H-35x40 -02	35	25	33	115	62	22	M28x1,5 L	M18x1,5	80	26	40°	1,330
AH32-2H-40x40 -01	40	28	37	120	69	26	M30x1,5 R	M20x1,5	80	30	40°	1,600
AH32-2H-40x40 -02	40	28	37	120	69	26	M30x1,5 L	M20x1,5	80	30	40°	1,600
AH32-2H-50x45 -01	50	33	44	135	80	30	M30x1,5 R	M24x1,5	85	34	45°	2,800
AH32-2H-50x45 -02	50	33	44	135	80	30	M30x1,5 L	M24x1,5	85	34	45°	2,800

Lagerpaarung: Stahl / Stahl R (-01) = Rechtsgewinde / right hand thread (RH)
 Bearing design: steel / steel L (-02) = Linksgewinde / left hand thread (LH)