



HEYD BESTELL-No.	GRÖSSE/SIZE			Abmessungen in mm / Dimensions in mm										kg/Stück
	d1	a	b	c	d1	d2	d3	d4	d7	e	l	α		
AH39-1A-35x25 -01	35	25	32	115	35,5	62	26	M30x1,5 R	M20x1,5	80	30	40°	1,480	
AH39-1A-35x25 -02	35	25	32	115	35,5	62	26	M30x1,5 L	M20x1,5	80	30	40°	1,480	
AH39-1A-40x25 -01	40	28	36	120	40,7	69	30	M30x1,5 R	M24x1,5	80	34	40°	2,000	
AH39-1A-40x25 -02	40	28	36	120	40,7	69	30	M30x1,5 L	M24x1,5	80	34	40°	2,000	
AH39-1A-50x25 -01	50	30,5	42	135	47	80	38	M38x1,5 R	M30x1,5	85	42	40°	3,600	
AH39-1A-50x25 -02	50	30,5	42	135	47	80	38	M38x1,5 L	M30x1,5	85	42	40°	3,600	
AH39-1A-65x25 -01	65	40,5	54,5	160	66	105	45	M38x1,5 R	M39x1,5	95	50	40°	6,000	
AH39-1A-65x25 -02	65	40,5	54,5	160	66	105	45	M38x1,5 L	M39x1,5	95	50	40°	6,000	
AH39-1-80x25 -01	80	50	63	200	80	120	56	M48x1,5 R	M48x1,5	115	63	40°	9,480	
AH39-1-80x25 -02	80	50	63	200	80	120	56	M48x1,5 L	M48x1,5	115	63	40°	9,480	

Lagerpaarung: Stahl/Stahl R (-01) = Rechtsgewinde / right hand thread (RH)
 Bearing design: steel / steel L (-02) = Linksgewinde / left hand thread (LH)