



HEYD	GRÖßE / SIZE		Abmessungen in mm / Dimensions in mm										
BESTELL-No.	d1	a	b	c	d2	d3	d4	d6	e	h	l	α	kg/Stück
<b>AH89-1 66x30 -01</b>	66	165	130	190	105	43	M48x1,5 R	43	110	30	90	30°	6,200
<b>AH89-1 66x30 -02</b>	66	165	130	190	105	43	M48x1,5 L	43	110	30	90	30°	6,200
<b>AH89-2 66x30 -01</b>	66	190	152	190	105	43	M48x1,5 R	43	110	24	114	30°	6,100
<b>AH89-2 66x30 -02</b>	66	190	152	190	105	43	M48x1,5 L	43	110	24	114	30°	6,100
<b>AH89-3 66x30 -01</b>	66	165	130	190	105	43	M38x1,5 R	43	100	30	90	30°	5,700
<b>AH89-3 66x30 -02</b>	66	165	130	190	105	43	M38x1,5 L	43	100	30	90	30°	5,700
<b>AH89-4 66x30 -01</b>	66	185	152	190	105	48	M48x1,5 R	48	110	30	105	30°	5,600
<b>AH89-4 66x30 -02</b>	66	185	152	190	105	48	M48x1,5 L	48	110	30	105	30°	5,600

Lagerpaarung: Stahl / Stahl R (-01) = Rechtsgewinde / right hand thread (RH)  
 Bearing design: steel / steel L (-02) = Linksgewinde / left hand thread (LH)